

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION		
PRODUCT	:	AMPRO HYDRAULIC OIL ISO 46
CODE	:	AMPRO205
MANUFACTURER IDENTIFICATION	:	M/s United Grease And Lubricants P.O. Box 2685, Ajman, U.A.E.
BRAND OWNER	:	Al Maha Petroleum Products Marketing Company SAOG PO Box 57, Postal Code 116, Muscat, Sultanate of Oman
EMERGENCY PHONE NUMBER	:	00971-6-7436521
PRODUCT USE	:	HYDRAULIC OIL
COMPOSITION / INFORMATION ON INGREDIENTS		
CHEMICAL NAME	CAS NO	WT
Zinc dialkyl dithiophosphate	68649-42-3	0.6
alkyl phenol	Proprietary	0.2
Mineral oil	64741-88-4	99.2
HAZARDS IDENTIFICATION		
HAZARDS	:	UNDER NORMAL CONDITIONS OF USE, THIS PRODUCT SHOULD NOT CAUSE ANY SIGNIFICANT HEALTH HAZARDS. HOW EVER A PROLONGED USE MAY CAUSE DERMATITIS.
FIRST AID MEASURES :		
SKIN CONTACT	:	REMOVE CONTAMINATED CLOTHING, WASH SKIN IMMEDIATELY WITH WATER AND SOAP
EYE CONTACT	:	FLUSH WITH LARGE AMOUNT OF WATER, GET MEDICAL ATTENTION IF IRRITATION PERSISTS
INGESTION	:	DO NOT INDUCE VOMITING .GET MEDICAL ATTENTION
INHALATION	:	IN CASE OF EXPOSURE TO HIGH CONCENTRATION REMOVE PERSON TO FRESH AIR
FIRE FIGHTING MEASURES		
FLASH POINT	:	240 Deg C
EXTINGUISHING MEDIA	:	CO2, DRY CHEMICAL, OR FOAM.WATER SPRAY, DO NOT USE WATER JETS .THEY COULD CAUSE SPLATTERING.
ACCIDENTAL RELEASE MEASURES		
ENVIRONMENTAL PROTECTION	:	SHUT OFF SOURCE OF SPILL .RECOVER FREE LIQUIDS BY USING APPROPRIATE TECHNIQUES.NOTIFY LOCAL AUTHORITIES
HANDLING AND STORAGE	:	HANDLING AND STORAGE TEMP. AMBIENT TO 85 Deg C
EXPOSURECONTROLS/PERSONAL PROTECTION		
HAND/EYES/SKIN PROTECTION	:	WEAR GOGGLES, PROTECTIVE CLOTHING, GLOVES.
VENTILATION	:	NO SPECIAL VENTILATION REQUIRED

PHYSICAL AND CHEMICAL PROPERTIES	
APPEARANANCE	: C&B
ODOUR	: CHARACTERISTIC
COLOR	: GOLDEN
DENSITY @ 15 Deg	: 0.885Kg/L
FLASH POINT	: 240 Deg C
SOLUBLITY	: SOLUBLE IN HYDROCARBON SOLVENTS, INSOLUBLE IN WATER
STABILITY AND REACTIVITY	
STABILITY	: STABLE PRODUCT
HAZARDOUS REACTION	: NONE
ECOLOGICAL INFORMATION GENERAL	: NO SPECIFIC ENVIRONMENTAL DATA AVAILABLE
DISPOSAL CONSIDERATION	
DISPOSAL OF PRODUCT	: DO NOT DISPOSE OF THE PRODUCT EITHER NEW OR USED, BY DISCHARGING IN TO SEWERS, TUNNELS, LAKES OR WATER COURSES.
STORAGE CONDITIONS	: HANDLING AND STORAGE TEMP. AMBIENT TO 40 Deg C
SHELF LIFE	: 48 MONTHS AFTER THE DATE OF MANUFACTURING
TRANSPORT INFORMATION	
NOT DANGEROUS FOR CONVEYANCUNDER UN, IMO,ADR/ RID AND IATA/CAO CODES	: NOT REGULATED
REGULATORY INFORMATION	
SYMBOL[S]	NONE
R PHRASE[S]	NONE
S PHRASE[S]	NONE
OTHER INFORMATIONS:	
R-PHRASES LISTED IN CHAPTER 2	: R41 RISK OF SERIOUS DAMAGE TO EYES R51/53 TOXIC TO ACQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT
PRODUCT INFORMATION	: FOR SPECIFIC OR DETAILED TECHNICAL DATA FOR THIS PRODUCT, PLEASE CONTACT YOUR LOCAL SALES REPRESENTATIVE.
HAZARD RATINGS	: 4- Extreme 3- Serious 2- Moderate 1- Slight 0- Minimal See section 8 for more detailed Information on personal protection
The customer is responsible for determining the PPE code for this material	
NOTICE FOR READER	
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.	

The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC.